

92mm DC FAN
CE RS
● General Specifications

- ⊙ Material ----- Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- ⊙ Lead Wire ----- + Red - Black (Sensor) Yellow (Control) Brown
- ⊙ Life time -----25000 Hours Sleeve bearing
50000 Hours Ball bearing
- ⊙ Storage Temperatur--- -30℃ ~ +70℃ (Non-condensing)
- ⊙ Bearing Type----- Ball Bearings Sleeve
- ⊙ Speed Range----- ±10%
- ⊙ Part Numbering System


 SFD-FB0912HHE- **B R 1**

Waterproof level:0=no,1=IP55,2=IP68

Sensor: 0=no,R=RD sensor ,F=FG sensor ,P=PWM sensor ,T=Temperature sensor

Bearing:S=sleeve bearing,B=ball bearing,Y=superflo bearing,L=long life bearing

92 X 92 X 38mm (Mass: 180g)

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M3/min	CFM	MmH2O	IN H2O	dB-A
SFD-FB0912HHE	12	7.2-13.8	0.38	4.56	3300	2.01	71.60	7.56	0.296	43.0
SFD-FB0912VHE			0.54	6.48	3900	2.40	85.40	10.25	0.405	48.0
SFD-FB0912SHE			0.79	9.48	4500	2.83	99.85	14.42	0568	53.5
SFD-FB0912EHE			1.05	12.6	5000	3.10	109.85	16.78	0.659	56.5
SFD-FB0924HHE	24	14.5~27.5	0.21	5.04	3300	2.01	71.60	7.56	0.296	43.0
SFD-FB0924VHE			0.30	7.20	3900	2.40	85.40	10.25	0.405	48.0
SFD-FB0924SHE			0.43	10.32	4500	2.83	99.85	14.42	0568	53.5
SFD-FB0924EHE			0.54	12.96	5000	3.10	109.85	16.78	0.659	56.5
SFD-FB0948HHE	48	29.0~55.0	0.11	5.28	3300	2.01	71.60	7.56	0.296	43.0
SFD-FB0948VHE			0.15	7.20	3900	2.40	85.40	10.25	0.405	48.0
SFD-FB0948SHE			0.22	1056	4500	2.83	99.85	14.42	0568	53.5

● Dimensions(unit:mm\inch)
● Air Flow-Static Pressure Characteristics
